Revised January 2002



9411 Corsair Road Frankfort, IL 60423 1-800-552-0299 Phone 1-815-464-5650 Fax

EMERGENCY PHONE 1-800-255-3924

MATERIAL SAFETY DATA SHEETS TORQUE 40 RC

HMIS; HEALTH 2 FLAMMABILITY 1 REACTIVITY 1 NFPA HEALTH 2 FIRE HAZARD 1 REACTIVITY 1

1. GENERAL INFORMATION

PRODUCT NAME: Torque 40RC TECHINCAL NAME: Anaerobic

2. COMPOSITION/INFORMATION ON INGREDIENTS

CAS No. 용 Ingredients Aromatic dimethacrylate 24448-20-2 40-60 Polyglycol dimethacrylate 109-16-0 20 - 40Hydroxyalkyl methacrylate 27813-02-1 5-15 Acrylic acid* 79-10-7 2 - 480-15-9 Oic peroxide* 1-2 81-07-02 Benzoic sulphimide

Ingredients which have exposure limits

Exposure Limits (TWA) ACGIH OSHA OTHER

Ingredients (TLV) (PEL)

Organic peroxide None None 1ppm(6mg/m3)
Skin(WEEL)
Hydroxyalkyl methacrylate None None 1 ppm TWA

Acrylic acid 2 ppm TWA skin 10 ppm TWA skin 1 ppm TWA skin 1 ppm TWA skin

2 ppm TWA skin 10 ppm TWA skin 1 ppm TWA skin 5.9 mg/m3 skin 30 mg/m3 skin 3 ppm STEL skin

3. HAZARD IDENTIFICATION

Toxicity: Liquid and Vapors are an eye and skin irritant.

Primary Routes of Entry: None known

Signs and Symptoms of Exposure: May cause dermatitis on prolonged contact in

sensitive individuals.

Existing Conditions Aggravated by Exposure: Acrylic acid: Upper respiratory and lung diseases,

dermatitis

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Keep individual calm.

Obtain medical attention.

Inhalation:

Does not apply

Inhalation: Does not apply Skin Contact: Wash with soap and water.

Eye Contact: Flush at least 15 minutes with plenty of water. Obtain

medical attention.

None

5. FIREFIGHTING MEASURES

by Fire or Thermal Decomp Irritating organic vapors

Flash Point: More than 200°F

Extinguishing Agents: Carbon dioxide, foam, dry chemical

Special Firefighting
Procedures:

Not available

Hazardous Products formed

Unusual Fire or Explosion Hazards:

^{*} This component is listed as a SARA Section 313 Toxic Chemical.



MATERIAL SAFETY DATA SHEETS TORQUE 40 RC



6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case of spill or leak:

Soak up with an inert absorbent. Store in closed container

until disposal.

7. HANDLING AND STORAGE

Safe Storage: Handling: Store at or below 100°F

Avoid prolonged contact with eyes and skin.

8. EXPOSURE AND PERSONAL PROTECTION

Eyes:

Skin:

Ventilation: Respiratory Safety glasses or goggles.

Neoprene, rubber, or butyl rubber gloves.

Does not apply Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Odor:

Boiling Point:

pH:

Solubility in Water: Specific Gravity Vapor Pressure:

Vapor Density: Evaporation Rate Green Liquid Sharp irritating

More than 300°F Does not apply

Slight

1.1 at 25°C

Less than 0.5 mmbar at 20°C

Not available Not available

10. REACTIVITY

Stability:

Hazardous Polymerization: Incompatibility: Conditions to Avoid:

Hazardous Decomposition Products (non-thermal):

Stable Will not occur

None

Not available

None

11. TOXICOLOGICAL INFORMATION

Estimated oral LD50 more than 5000 mg/kg. Estimated dermal LD50 more than 2000 mg/kg.

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended methods of disposal: EPA Hazardous Waste Number

Incinerate following EPA and local regulations. NH - Not a RCRA Hazardous Waste Material



MATERIAL SAFETY DATA SHEETS TORQUE 40 RC



14. TRANSPORTATION INFORMATION

DOT (49 CFR 172)
Domestic Ground Transport
Proper Shipping Name:
Hazard Class or Division:
Identification Number:
Marine Pollutant:
IATA
Proper Shipping Name:
Class or Division:
UN or ID Number:

Unrestricted Unrestricted None None

Unrestricted Unrestricted None

Engineering Excellence

For technical information and support call 1-800-552-0299 or visit our website at

