Revised January 2002



9411 Corsair Road Frankfort, IL 60423 1-800-552-0299 Phone 1-815-464-5650 Fax

### **EMERGENCY PHONE 1-800-255-3924**

# MATERIAL SAFETY DATA SHEETS **TORQUE 48 RC**

HMIS; **HEALTH** 2 **FLAMMABILITY** REACTIVITY 1 1 **NFPA HEALTH** 2 FIRE HAZARD 1 REACTIVITY 1

#### 1. GENERAL INFORMATION

Organic peroxide\*

PRODUCT NAME: Torque 48RC TECHINCAL NAME: Anaerobic

CAS No.

80-15-9

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients Aromatic dimethacrylate 24448-20-2 60-70 Bisphenol A fumarate resin 39382-25-7 10-20 Hydroxyalkyl methacrylate 27813-02-1 10-20 Acrylic acid\* 79-10-7 1-5

\* This component is listed as a SARA Section 313 Toxic Chemical.

Ingredients which have exposure limits

Exposure Limits (TWA) ACGIH OSHA OTHER

Ingredients (TLV) (PEL)

1ppm(6mg/m3) Organic peroxide None None

> Skin (WEEL) None None 1 ppm TWA

용

3 ppm STEL

Acrylic acid 2 ppm TWA skin 10 ppm TWA skin 1 ppm TWA skin 5.9 mg/m3 skin 30 mg/m3 skin 3 ppm STEL skin

#### 3. HAZARD IDENTIFICATION

Hydroxyalkyl methacrylate

Toxicity: Liquid and Vapors are an eye and skin irritant.

Primary Routes of Entry: None known

Signs and Symptoms of Exposure: May cause dermatitis on prolonged contact in sensitive individuals.

Existing Conditions Aggravated by Exposure: Acrylic acid: Upper respiratory and lung diseases,

dermatitis

#### 4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Keep individual calm.

Obtain medical attention.

Inhalation: Does not apply

Skin Contact: Wash with soap and water.

Flush at least 15 minutes with plenty of water. Obtain Eve Contact: medical attention.

#### 5. FIREFIGHTING MEASURES

by Fire or Thermal Decomp Irritating organic vapors

Flash Point: More than 200°F

Extinguishing Agents: Carbon dioxide, foam, dry chemical Special Firefighting

Procedures: Not available

Hazardous Products formed

Unusual Fire or Explosion Hazards: None



# MATERIAL SAFETY DATA SHEETS **TORQUE 48 RC**



### 6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case of spill or leak:

Soak up with an inert absorbent. Store in closed container

until disposal.

#### 7. HANDLING AND STORAGE

Safe Storage: Handling:

Store at or below 100°F

Avoid prolonged contact with eyes and skin.

#### 8. EXPOSURE AND PERSONAL PROTECTION

Eyes:

Skin:

Ventilation: Respiratory Safety glasses or goggles.

Neoprene, rubber, or butyl rubber gloves.

Does not apply Not available

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Odor:

**Boiling Point:** 

Solubility in Water:

Specific Gravity Vapor Pressure:

Vapor Density: **Evaporation Rate**  Green Liquid

Sharp irritating More than 300°F

Does not apply Slight

1.1 at 25°C

Less than 0.5 mmbar at 20°C

Not available Not available

## 10. REACTIVITY

Stability:

Hazardous Polymerization:

Incompatibility:

Conditions to Avoid:

Hazardous Decomposition

Products (non-thermal):

Stable

Will not occur

None

Not available

None

### 11. TOXICOLOGICAL INFORMATION

Estimated oral LD50 more than 5000 mg/kg. Estimated dermal LD50 more than 2000 mg/kg.

#### 12. ECOLOGICAL INFORMATION

No data available

#### 13. DISPOSAL CONSIDERATIONS

Recommended methods of disposal: EPA Hazardous Waste Number

Incinerate following EPA and local regulations. NH - Not a RCRA Hazardous Waste Material



# MATERIAL SAFETY DATA SHEETS TORQUE 48 RC



#### 14. TRANSPORTATION INFORMATION

DOT (49 CFR 172)
Domestic Ground Transport
Proper Shipping Name:
Hazard Class or Division:
Identification Number:
Marine Pollutant:
IATA
Proper Shipping Name:
Class or Division:

UN or ID Number:

Unrestricted Unrestricted None None

Unrestricted Unrestricted None

# Engineering Excellence

For technical information and support call **1-800-552-0299** or visit our website at

