Revised January 2002



9411 Corsair Road Frankfort, IL 60423 1-800-552-0299 Phone 1-815-464-5650 Fax

EMERGENCY PHONE 1-800-255-3924 MATERIAL SAFETY DATA SHEETS AS 201 PREMIUM ANTI-SEIZE

1. GENERAL INFORMATION

| PRODUCT NAME: | | | AS 201 | | | | |
|--------------------------|-------------|-----------|----------------------------------|----------|--------|---------|--|
| CHEMIC AL FAMILY: | | | Anti-Seize Lubricating Compounds | | | | |
| 2. COMPOSITION | CAS # | OSHA/PEL | TLV | SARA III | PROP65 | PERCENT | |
| COPPER,ASDUSTORFUME | 7440-50-6 | 1m91m3 | SAME | YES | NO | 20-30 | |
| ALUMINUM, AS DUST OR FUM | E 7429-90-5 | 5mg/m3 | SAME | NO | NO | 5-8 | |
| PETROLEUM OIL | 64742-65-0 | Smg/m3 | SAME | NO | NO | 40-60 | |
| GRAPHITE | 7782-42-5 | 2 5 mg!m3 | SAME | NO | NO | 20-30 | |
| 3. PHYSICAL PROPERTIES | 6 | | | | | | |

BOILING POINT: DOES NOT APPLY MELTING POINT: DOES NOT APPLY VAPOR PRESSURE: NO DATA EVAPORATION RATE: 0 APPEARANCE AND ODOR: SILVER/GRAY PASTE. GREASE LIKE ODOR

4. FIRE AND EXPLOSION DATA

FLASH POINT AND METHOD USED: FLAMMABLE LIMITS: EXTINGUISHING MEDIA: SPECIAL FIRE FIGHTING PROCEDURES: SOLUBILITY IN WATER: NIL REACTIVITY IN WATER: NONE SPECIFIC GRAVITY: 1 2 PERCENT VOLATILE: 0

> 350F, C.O C LEL. NO DATA UEL: NO DATA FOAM, C02, DRY CHEMICAL THIS COMPOUND WILL NOT BURN UNLESS IT IS PRE-HEATED WATER FOG MAY BE USED TO COOL THE CONTAINERS BUT DO NOT SPRAY DIRECTLY INTO LARGE CONTAINERS OF BURNING LIQUI9S AS FROTHING MAY OCCUR WEAR A N.I.O.S.H. APPROVED ORGANIC VAPOR RESPIRATOR DENSE SMOKE AND NOXIOUS OR TOXIC FUMES MAY BE GENERATED IN A FIRE FIRE FIGHTERS SHOULD WEAR A SELF CONTAINED BREATHING APPARATUS

UNUSUAL FIRE AND EXPLOSION HAZARDS:

5. PHYSICAL HAZARDS

STABILITY: CONDITIONS TO AVOID: INCOMPARABILITY: HAZARDOUS DECOMPOSITION PRODUCTS:

STABLE

TEMPERATURES EXCEEDING 550 F STRONG OXIDIZING AGENTS THE THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDENT UPON THE COMBUSTION CONDITIONS NOXIOUS OR TOXIC FUMES MAY BE GENERATED, SOME OF WHICH MAY BE TOXIC OR IRRITATING WILL NOT OCCUR

HAZARDOUS POLYMERIZATION:

6. HEALTH HAZARDS AND FIRST AID HEALTH HAZARDS:

THIS PRODUCT IS NOT PARTICULARLY TOXIC AS WITH ANY PETROLEUM BASED PRODUCT, SKIN IRRITATION CAN OCCUR IF PROLONGED OR REPEATED SKIN CONTACT OCCURS KEEP OUT OF OPEN WOUNDS AVOID BREATHING LARGE QUANTITIES OF THE THERMAL DECOMPOSITION FUMES

| | MATERIAL SAFETY DATA SHEETS AS 201 PREIMIUM |
|-------------|---|
| SKIN: | WASH WITH SOAP AND WATER, USING A NAIL BRUSH PAY PARTICULAR ATTENTION TO FINGER NAILS AND OFEN WOUNDS |
| EYES: | THIS PRODUCT COULD CAUSE SOME MECHANICAL IRRITATION IF GOTTEN INTO THE EYES AND RUBBED FLUSH EYE WITH WATER FOR 15 MINUTES, LIFTING THE EYELIDS IF IRRITATION PERSISTS CONSULT A PHYSICIAN |
| INGESTION: | IF INGESTED THIS PRODUCT IS NDT EXPECTED TO CAUSE AN ACUTE REACTION THIS PRODUCT CONTAINS A PETROLEUM OIL, DO NOT INDUCE VOMITING, BECAUSE THE OIL MAY BE ASPIRATED INTO THE LUNGS USE A GASTRIC LAVAGE, AND CALL A POISON CONTROL CENTER OR A PHYSICIAN |
| INHALATION: | NOT LIKELY UNDER NORMAL CONDITIONS OF USE IF USING IN HIGH TEMPERATURE APPLICATIONS WHERE THERMAL DECOMPOSITION IS LIKELY, USE A LOCAL EXHAUST TO REMOVE FUMES IF DIZZINESS OR IRRITATION OCCURS, SEEK FRESH AIR |

7. SPECIAL PRECAUTIONS AND SPILL PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE AWAY FROM STRONG OXIDIZERS, EXTREME HEAT OR OPEN FLAMES KEEP AWAY FROM CHILDREN

OTHER PRECAUTIONS: DO NOT TRANSFER TO UNMARKED CONTAINERS KEEP AWAY FROM CHILDREN

SPILL/LEAKAGE PROCEPURES: BECAUSE OF ITS VISCOUS NATURE THIS PRODUCT IS NOT EXPECTED TO LEAK OR SPILL SMALL SPILLS MAY BE SCOOPED UP AND RETURNED TO THE CONTAINER

WASTE DISPOSAL: DISPOSE OF IN A RESPONSIBLE MANNER FOLLOW LOCAL STATE, AND FEDERAL GUIDELINES DO NOT DISCHARGE INTO SEWERS OR WATERWAYS INCINERATION IS THE PREFERRED METHOD OF DISPOSAL, ALTHOUGH IT MAY BE LANDFILLED AT AN APPROVED FACILITY

8. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NORMALLY NOT REQUIRED, IF THIS PRODUCT IS BEING USED IN HIGH TEMPERATURE APPLICA110N WHERE THE PRODUCT "SMOKES' USE A LOCAL EXHAUST OR VENTILATE THE AREA TO MAINTAIN THE AIR OUALITY, OR USE A "NIOSH" APPROVED ORGANIC VAPOR RESPIRATOR IF AN INDIVIDUALS REMOVING, DRY, FLAKY MATERIAL! USE A DUST RESPIRATOR

PROTECTIVE GLOVES: NORMALLY NOT REQUIRED IF PROLONGED OR REPEATED SKIN CONTACT IS EXPECTED USE A LATEX GLOVE

EYE PROTECTION: SAFETY GLASSES ARE RECOMMENDED

WORK/HYGIENIC PRACTICES: USE GOOD STANDARD PRACTICES WHEN USING THIS MATERIAL DO NOT EAT OR SMOKE WHILE USING, AND THOROUGHLY WASH WITH SOAP AND WATER, USING A NAIL BRUSH AFTER USING

9. REGULATORY INFORMATION

CALIFORNUA PROPOSITION 85: OZONE DEPLETING SUBSTANCES: NONE SARA TITLE III: COPPER CERCLA:COPPER RCRA: NO DOT SHIPPING CLASS: NOT HAZARDOUS TASCA INVENTORY: ALL INGREOJANTS LISTED NFPA RATING: H-1,F-0,R-O

Engineering Excellence

For technical information and support call **1-800-552-0299** or visit our website at

