

Revised
November 2003



9411 Corsair Road
Frankfort, IL 60423
1-800-552-0299 Phone
1-815-464-5650 Fax

EMERGENCY PHONE 1-800-255-3924

MATERIAL SAFETY DATA SHEETS

MP 5257

HMIS	HEALTH	2	FLAMMABILITY	1	REACTIVITY	0
NFPA	HEALTH	2	FIRE HAZARD	1	REACTIVITY	0

1. GENERAL INFORMATION

PRODUCT NAME: MP 5257
TECHINICAL NAME: Adhesive to be used with Activator
CHEMICAL NAME: Methacrylate esters composition

2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT:	%
Tetra Ethylene Glycol Di Methacrylate	65%
Saccharin	.5% - 4.0%
NN Di Alkyltoluidine	1%
Resin	30%

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >212°F (method used C.O.C.)
FLAMMABLE LIMITS: LEL=N/A UEL=N/A
EXTINGUISHING MEDIA: Carbon Dioxide, dry chemicals, water
SPECIAL FIRE FIGHTING PROCEDURES: NONE
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

4. HEALTH HAZARD DATE:

EFFECTS OF OVEREXPOSURE: Prolong skin contact may result in Dermatitis in sensitive persons. Will irritate eyes on contact. Wash with soap and water for skin contact. For eye contact flush with plenty of water. For ingestion, DO NOT induce vomiting. Contact a physician.

5. RECTIVITY DATA

STABILITY:	Stable
CONDITIONS TO AVOID:	Strong reducing agent or heat exposure.
INCOMPAIBILITY:	Keep containers cool with water spray.
HAZARDOUD DECOMPOSITION:	None
HAZARDOUD POLYMERIZATION:	May occur
CONDITIONS TO AVOID:	Temperature in excessive of 150°F

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:	Soak up with inert absorbent
WATER DISPOSAL METHOD:	Bury or incinerate in accordance with EPA local regulations.

7. SPECIAL PROTECTION INFORMATION

RESPIRATORY:	None needed for normal use
VENTILATION:	Adequate in-plant air movement is sufficient
GLOVE:	Polyethylene gloves
EYE:	Safety Glasses

8. SPECIAL PRECAUTIONS

Store in a cool, dry place, out of direct sunlight. **KEEP AWAY FOR CHILDREN**



MATERIAL SAFETY DATA SHEETS

MP 5257



9. PHYSICAL AND CHEMICAL PROPERTIES:

ODOR:	Mild Odor
APPERANCE:	Amber
SPECIFIC GRAVITY:	1.10-1.15
BOILING POINT:	>400°F
SOLUBILITY IN WATER:	Insluble
VAPOR DENSITY:	1.01
VAPOR PRESSURE:	.01 (mmHg)
PERCENT VOLATILE:	<1%

14. TRANSPORTATION INFORMATION:

WAY	CLASS	LABEL
ROAD-RAIL	ADR/RID	NC
SEA	IMO/IMDG	NC
AIR	ICAO/IATA	NC

(NOTE: NC = NOT CLASSIFIED. SPECIAL LABELING NOT REQUIRED.)

Engineering Excellence

For technical information
and support call **1-800-552-0299** or visit our website at

www.instantca.com