

Revised
January 2004



9411 Corsair Road
Frankfort, IL 60423
1-800-552-0299 Phone
1-815-464-5650 Fax

EMERGENCY PHONE 1-800-255-3924

MATERIAL SAFETY DATA SHEETS

MP 54270 RESIN PART A

HMIS	HEALTH	2	FLAMMABILITY	1	REACTIVITY	0
NFPA	HEALTH	2	FIRE HAZARD	1	REACTIVITY	0

1. GENERAL INFORMATION

PRODUCT NAME:	MP 54270 - RESIN PART A
CHEMICAL FAMILY:	Epoxy Resin
CHEMICAL NAME:	Mixture

2. COMPOSITION

NAME	CAS #	OSHA PEL	ACIGH TLV
EPOXY RESIN	025-085-99-8	NA	NA
Urethane Polymer	NA	NA	NA
Aliphatic Triglyceride Triglycidyl Ether	074398-71-3	NE	NE
CARBON BLACK	1333-86-4	3.5mg/m3	3.5mg/m3

3. CHEMICAL AND PHYSICAL PROPERTIES

FLASH POINT (PMCC) >200F	BOILING POINT >200F
VAPOR DENSITY > AIR	EVAPORATION RATE NIL
% VOLATILE BY VOL. 0	SPECIFIC GRAVITY 1.15
SOLUBILITY IN WATER: NEGLIGIBLE	VAPOR PRESSURE < 1mm Hg
APPEARANCE AND ODOR: BLACK LIQUID, MILD EPOXY ODOR	

4. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	>200°F
FLAMMABLE LIMITS:	LEL=N/A UEL=N/A
EXTINGUISHING MEDIA:	Water fog, carbon dioxide, foam or dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES:	Full protective equipment including self-contained breathing apparatus should be used. Water spray may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Keep containers tightly closed. Water may be used to cool unruptured containers.

5. HEALTH HAZARD DATA

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:	Preexisting disorders of the skin and/or eyes.
EYE CONTACT:	Contains ingredients which are irritating to the eyes. Symptoms may include blurred vision, burning sensation and tearing.
SKIN CONTACT:	Contains materials which cause moderate skin irritation. This product may cause skin sensitization or allergic reactions which may be severe with certain people. Symptoms include rash, itching, hives and swelling of extremities. Prolonged or repeated exposure may cause a defatting or drying action to skin.
INHALATION:	Unlikely at room temperature due to low volatility, however heating can generate vapors that may cause respiratory irritation.
INGESTION:	Product is harmful if swallowed



MATERIAL SAFETY DATA SHEETS

MP 54270 RESIN PART A



6. REACTIVITY DATA

HAZARDOUS POLYMERIZATION:
CONDITIONS TO AVOID:
MATERIALS TO AVOID:

Will not occur.
High temperatures, high humidity.
STRONG OXIDIZING AGENTS; STRONG ACIDS OR BASES.

7. SPILL OR LEAK PROCEDURES

SPILLS:
WASTE DISPOSAL METHOD:

Contain and remove with absorbent material. Avoid contact. **Disposal should be done in accordance with Federal (40 CFR Part 261), State and local regulations. Before attempting clean-up, refer to hazard caution information in other sections of the MSDS form. Use only licensed hazardous waste disposal companies.**

8. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

Use approved chemical/mechanical filters designed to remove a combination of particulates and organic vapors in open and restricted areas when ventilation does not meet the requirements of 29 CFR 1910.134. Use approved airline type respirators or hoods in confined areas.

VENTILATION:

Sufficient ventilation in pattern and volume to keep the air contaminant concentration below applicable exposure limits. All application areas should be ventilated in accordance with OSHA regulation 29 CFR 1910.134

PROTECTIVE GLOVES:

Use neoprene or other impervious gloves to prevent skin contact.

EYE PROTECTION:
OTHER PROTECTIVE EQUIPMENT:

Use safety glasses with side shields as minimum protection. Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

HYGENIC PRACTICES:

Wash hands before eating, smoking or using toilet facilities. Do not smoke in any chemical handling and storage area. Food or beverages should not be consumed anywhere near this product is handled or stored.

9. SPECIAL PRECAUTIONS

STORAGE TEMPERATURE:
AVERAGE SHELF LIFE:
STORAGE:
OTHER:

40-80°F
12 Months in original sealed container
DO NOT store near heat or open flame.
Empty container should not be reused.

10. TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME:
HAZARD CLASS OR DIVISION:
PACKING GROUP NUMBER:
REQUIRED LABEL:

NOT REGULATED
NA
NA
NONE

Engineering Excellence

For technical information
and support call **1-800-552-0299** or visit our website at

www.instantca.com

Revised
January 2002



9411 Corsair Road
Frankfort, IL 60423
1-800-552-0299 Phone
1-815-464-5650 Fax

EMERGENCY PHONE 1-800-255-3924

MATERIAL SAFETY DATA SHEETS

MP 54270 RESIN PART B

HMIS;	HEALTH	3	FLAMMABILITY	1	REACTIVITY	0
NFPA	HEALTH	3	FIRE HAZARD	1	REACTIVITY	0

1. GENERAL INFORMATION

PRODUCT NAME:	MP 54270 - RESIN PART B
CHEMICAL FAMILY:	Polyamine Blend
CHEMICAL NAME:	Polyethylenepolyamine Mixture

2. COMPOSITION

INGREDIENT:	CAS#	%	TLV-TWA	PEL
POLYAMIDE RESIN*	NA	50	NA	NA
N-AMINOETHYL PIPERAZINE	140-31-8	30	NA	NA
NONYL PHENOL	84852-15-3	20	NE	NE

3. CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE:	Amber Liquid
ODOR:	Mild Amine odor.
SPECIFIC GRAVITY:	0.99
BOILING POINT:	>200°F
SOLUBILITY IN WATER:	Slight
VAPOR DENSITY:	>Air
COLOR:	Amber
VAPOR PRESSURE :	<1mm Hg

4. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	>200°F
FLAMMABLE LIMITS:	LEL=N/A UEL=N/A
EXTINGUISHING MEDIA:	Water fog, carbon dioxide, foam or dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES:	Full protective equipment including self-contained breathing apparatus should be used. Water spray may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Keep containers tightly closed. Water may be used to cool unruptured containers.

5. HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:	Primarily redness and irritation.
ACUTE: SKIN;	May cause skin sensitization.
CHRONIC:	Symptoms may include burning sensation, coughing and shortness of breath.
ACUTE: INHALATION;	

6. REACTIVITY DATA

HAZARDOUS POLYMERIZATION:	Will not occur.
CONDITIONS TO AVOID:	High temperatures, high humidity.
MATERIALS TO AVOID:	STRONG OXIDIZING AGENTS; STRONG ACIDS OR BASES.



MATERIAL SAFETY DATA SHEETS

MP 54270 RESIN PART B



7. SPILL OR LEAK PROCEDURES

SPILLS:

WASTE DISPOSAL METHOD:

Contain and remove with absorbent material. Avoid contact. **Disposal should be done in accordance with Federal (40 CFR Part 261), State and local regulations. Before attempting clean-up, refer to hazard caution information in other sections of the MSDS form. Use only licensed hazardous waste disposal companies.**

8. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

VENTILATION:

PROTECTIVE GLOVES:

EYE PROTECTION:

OTHER PROTECTIVE EQUIPMENT:

HYGENIC PRACTICES:

Avoid breathing vapors/mists. Use approved chemical/mechanical filters designed to remove a combination of particulates and organic vapors in open and restricted areas when ventilation does not meet the requirements of 29 CFR 1910.134. Use approved airline type respirators or hoods in confined areas. Sufficient ventilation in pattern and volume to keep the air contaminant concentration below applicable exposure limits. All application areas should be ventilated in accordance with OSHA regulation 29 CFR 1910.134. Use neoprene or other impervious gloves to prevent skin contact. Use safety glasses with side shields as minimum protection. Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes. Wash hands before eating, smoking or using toilet facilities. Do not smoke in any chemical handling and storage area. Food or beverages should not be consumed anywhere near this product is handled or stored.

9. SPECIAL PRECAUTIONS

STORAGE TEMPERATURE:

AVERAGE SHELF LIFE:

STORAGE:

OTHER:

SPECIAL SENSITIVITY:

20-80°F

12 Months in original sealed container

DO NOT store near heat or open flame.

Empty container should not be reused.

Moisture and Excessive heat.

10. TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME:

HAZARD CLASS OR DIVISION:

PACKING GROUP NUMBER:

REQUIRED LABEL:

Polyamines, liquid, corrosive, N.O.S. (N-aminoethyl piperazine, nonyl phenol)

8

III

CORROSIVE

11. EMERGENCY FIRST AID PROCEDURES

Move person to fresh air. Restore breathing. Treat symptomatically. Consult a physician.
(EYES)

(SKIN)

INGESTION:

Flush eyes with water for at least 15 minutes. Take to a physician for medical treatment.

Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists.

Drink one or two glasses of milk or water. Do not induce vomiting. Give medical attention immediately. Never give anything by mouth to an unconscious person.

Engineering Excellence

For technical information

and support call **1-800-552-0299** or visit our website at

www.instantca.com