

Revised
October 04, 2005



9411 Corsair Road
Frankfort, IL 60423
1-800-552-0299 Phone
1-815-464-5650 Fax

EMERGENCY PHONE 1-800-255-3924

MATERIAL SAFETY DATA SHEET
NI SERIES
CYANOACRYLATE ADHESIVE

HMIS	HEALTH	2	FLAMMABILITY	2	REACTIVITY	2
NFPA	HEALTH	2	FIRE HAZARD	2	REACTIVITY	2

1. Chemical Product

Product Name: NI Series
Product Type: Butyl Cyanoacrylate

2. Composition and Information on Harmful Ingredients

Ingredients	CAS No.	OSHA PEL	ACGIH TLV	Other Limits	%Composition
n-Butyl Cyanoacrylate	6606-65-1	N/A	N/A	N/A	>87
Hydroquinone	123-31-9	2mg/m ³ TWA	2mg/m ³ TWA	2mg/m ³ TWA	0.1-1

3. Hazards Identification

Label Precautionary Statements: Irritant. Irritating to eyes, skin, and respiratory system. Cyanoacrylate. Danger. Bonds skin and eyes in seconds.

Primary Routes of Entry: None Known

Symptoms of Exposure: Vapor irritating to eyes and breathing. Prolonged exposure may lead to non-allergic asthma.

Medical Conditions Aggravated by Exposure: No applicable information found.

Ethyl Cyanoacrylate is not listed as a carcinogen in the US National Toxicology Program Annual report on carcinogens, or by the International Agency for Research on Cancer.

4. First Aid Measures

Ingestion: Ingestion not likely due to polymerization.

Inhalation: Remove to fresh air, if symptoms continue, seek medical advice.

Skin Contact: Soak in warm soapy water.

Eye Contact: Flush with water, seek medical attention.



MATERIAL SAFETY DATA SHEET

NI SERIES

CYANOACRYLATE ADHESIVE



5. Fire Fighting Measures

Flash Point:	71- 94 °C
Extinguishing Media:	Water spray, foam, dry chemical or CO2.
Special Fire Fighting Procedures:	Wear self contained breathing apparatus.
Unusual Fire / Explosion Hazards:	No applicable information found.
Hazardous Thermal Decomposition Products:	Irritating organic vapors may be formed.

6. Accidental Release Measures

Ventilate area of spill, flood with water to polymerize, absorb with sand / earth and dispose to chemical waste bin. Dispose in accordance with pertinent national legislation.

7. Handling and Storage

When using large volumes ensure that operational area is well ventilated.
Store between 5- 25 °C; avoid strong light and heat sources.
Incompatible with amine, bases, water.
Avoid skin contact and inhalation of vapor.

8. Exposure Control and Personal Protection

Eye Protection:	Safety goggles / glasses suitable for use with chemicals.
Respiratory Protection:	Always use appropriate filter mask / respirator.
Skin Protection:	Nitrile / polyethylene gloves, coveralls, avoid cotton products.
Ventilation:	Good general or local exhaust ventilation is required for usage.

9. Physical and Chemical Properties

Form:	Liquid
Color:	Water white / straw colored
Odor:	Sharp, irritating
Solubility in Water:	Immiscible in water
Boiling Point:	>148 °C
Specific Gravity @ 25 °C:	1.05
Vapor Pressure @ 25 °C:	Less than 0.2mm
Flash Point:	71- 94 °C

10. Reactivity and Stability

Stability:	Stable
Hazardous Polymerization:	Will not occur
Incompatibility:	Water, bases, amines
Conditions to Avoid:	No applicable information found
Hazardous Decomposition Products:	No applicable information found



MATERIAL SAFETY DATA SHEET
NI SERIES
CYANOACRYLATE ADHESIVE



11. Toxicological Information

Estimated Oral LD50: >5000 mg kg

Estimated Dermal LD50: >2000 mg kg

Causes Severe Irritation. High concentrations are destructive to tissues of the mucous membranes and the upper respiratory tract.

12. Ecological Information

No applicable information found

13. Disposal Considerations

Cyanoacrylates must be disposed of in accordance with all national and local regulations.

14. Transportation Information

Not considered hazardous for the purposes of transportation.

NON- WARRANTY: Information contained herein is based on tests we believe to be reliable and accurate. It is offered in good faith for the benefit of the consumer. Adhesive Systems shall not be liable for any injury, loss, or damage in the use of it's chemical products since the conditions of use are beyond our control. In every case we urge and recommend the user conduct tests to determine to their own satisfaction that the product is of acceptable quality and is suitable for their particular purpose under their own operating conditions. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent. Because of changing reporting requirements and other variables it is impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to determine proper personal protection based on the actual condition of use and to comply with all Federal, State, and Local laws and regulations.

Engineering Excellence

For technical information

and support call **1-800-552-0299** or visit our website at

www.instantca.com