

Revised
January 2004



9411 Corsair Road
Frankfort, IL 60423
1-800-552-0299 Phone
1-815-464-5650 Fax

EMERGENCY PHONE 1-800-255-3924

TECHNICAL DATA SHEETS

POLY PREP PRIMER 2

Description:

POLY PREP PRIMER 2 is used for difficult to bond surfaces. **POLY PREP PRIMER 2** can be applied by brushing, spraying, or parts may be dipped prior to assembly. **POLY PREP PRIMER 2** is used for polyethylene, polypropylene, Teflon, delrin, certain elastomers, or other difficult to bond substrates. **POLY PREP PRIMER 2** is a single component, ready to use material. Simply apply it to the surface you wish to bond, wait 30 seconds, and the parts are ready for assembly. This material contains no CFC'S.

Physical Properties:

COLOR:	Clear/Amber
VISCOSITY:	3 cps
BASE:	Isopropyl Alcohol
ORDOR:	Light Chemical
FLASH POINT:	14 °F
SPECIFIC GRAVITY:	0.699 (@60°F)
BOILING POINT:	200-211°F

POLY PREP PRIMER 2 is available in 2 ounce, 8 ounce, and 1 gallon containers.

Engineering Excellence

For technical information
and support call **1-800-552-0299** or visit our website at

www.instantca.com