

Revised
January 2003



9411 Corsair Road
Frankfort, IL 60423
1-800-552-0299 Phone
1-815-464-5650 Fax

EMERGENCY PHONE 1-800-255-3924

MATERIAL SAFETY DATA SHEETS

PRIMER SF

HMIS	HEALTH	2	FLAMMABILITY	2	REACTIVITY	0
NFPA	HEALTH	2	FIRE HAZARD	2	REACTIVITY	0

1. GENERAL INFORMATION

PRODUCT NAME: PRIMER SF
CHEMICAL FAMILY: Activator

2. COMPOSITION

Ingredients	CAS No.	%
Hydroxyalkyl methacrylate	27813-02-1	90-95
2-Ethylhexanoic acid	149-57-5	1-3
Organo-copper compound	22221-10-9	1-3
Trialkylammonium Carboxylate	58823-74-8	1-3

Ingredients which have exposure limits

Exposure Limits (TWA) Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
Hydroxyalkyl methacrylate	None	None	1 ppm TWA 3 ppm STEL
2-Ethylhexanoic acid	5 mg/m ³ resp fr vapor/aerosol	None	None
Organo-copper compound	Cu 0.2mg/m ³ fume Cu 1 mg/m ³ dust	Cu 0.1mg/m ³ Cu 1 mg/m ³ dust	None

Exposure Limits (STEL) Ingredients	ACGIH (TLV)	OSHA (PEL)
---------------------------------------	----------------	---------------

3. HAZARD PROPERTIES

Toxicity:	Severe eye irritant. Moderate skin irritant. Possible inhalation irritant. May be harmful if swallowed. May cause kidney or liver damage. Estimated oral LD50 more than 5000 mg/kg. Estimated dermal LD50 more than 2000 mg/kg.
Primary Routes of Entry:	Eye, skin, inhalation, ingestion.
Signs and Symptoms of Exposure:	May cause severe dermatitis on prolonged contact in sensitive individuals.
Existing Conditions Aggravated by Exposure:	none.

4. FIRST AID MEASURES

Ingestion:	Do not induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation:	Remove to fresh air. If symptoms persist, obtain medical attention
Skin Contact:	Wash with soap and water.
Eye Contact:	Flush at least 15 minutes with water. Obtain medical attention.



MATERIAL SAFETY DATA SHEETS

PRIMER SF



5. FIRE FIGHTING PROCEDURES

Flash Point: More than 200°F Method: Pinsky Martens Closed Cup
Recommended Extinguishing Agents: Carbon dioxide, foam, dry chemical
Special Firefighting Procedures: Not available
Hazardous Products formed
by Fire or Thermal Decomp Irritating organic vapors; oxides of carbon.
Unusual Fire or Explosion Hazards: None
Explosive Limits:

(% by volume in air)Lower Not available
(% by volume in air)Upper Not available

6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case of spill or leak: Soak up in an inert absorbent. Store in a partly filled, closed container until disposal

7. HANDLING AND STORAGE

Safe Storage: Store below 100°F
Handling: Avoid skin contact. Keep away from eyes.
Avoid prolonged breathing of vapors.

8. PERSONAL PROTECTION

Eyes: Safety glasses or goggles.
Skin: Nitrile or neoprene gloves.
Ventilation: Sufficient to maintain vapor concentration below TLV.

Respiratory: Not available

See Section 2 for Exposure Limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: liquid
Odor: Slightly acrylic
Boiling Point: 158°F at 1mm
pH: Approximately 5
Solubility in Water: Moderate
Specific Gravity: 1.035 at 77°F
Volatile Organic Compound
(EPA Method 24) 97%; 1005 grams per liter
Vapor Pressure: 0.05mm at 68°F
Vapor Density: Approximately 1
Evaporation Rate
(Ether = 1) Not available

10. REACTIVITY

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: Oxidizing and reducing agents.
Conditions to Avoid: Not available
Hazardous Decomposition
Products (non-thermal): None

11. TOXICOLOGY INFORMATION

See Section 3.



MATERIAL SAFETY DATA SHEETS

PRIMER SF



12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL INFORMATION

Recommended methods of disposal:
EPA Hazardous Waste Number

Incinerate following EPA and local regulations.
NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49 CFR 172)
Domestic Ground Transport
Proper Shipping Name:
Hazard Class or Division:
Identification Number:
Marine Pollutant:
IATA
Proper Shipping Name:
Class or Division:
UN or ID Number:

Unrestricted
Unrestricted
None
None
Unrestricted
Unrestricted
None

Engineering Excellence

For technical information
and support call **1-800-552-0299** or visit our website at

www.instantca.com

