

Revised
January 2002



9411 Corsair Road
Frankfort, IL 60423
1-800-552-0299 Phone
1-815-464-5650 Fax

EMERGENCY PHONE 1-800-255-3924

MATERIAL SAFETY DATA SHEETS

TORQUE 170

HMIS	HEALTH	1	FLAMMABILITY	1	REACTIVITY	1
NFPA	HEALTH	1	FIRE HAZARD	1	REACTIVITY	1

1. GENERAL INFORMATION

PRODUCT NAME: Torque 170
TECHINICAL NAME: Anaerobic

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS No.	%
Urethane Dimethacrylate resin	Proprietary	40-60
Polyglycol dimethacrylate	25852-47-5	10-20
Bisphenol A fumarate resin	39382-25-7	10-20
Polyglycol Dioctanoate	18268-70-7	10-20
Alkyl methacrylate	27813-02-1	5-10
Benzoic sulphimide	81-07-2	1-3
Organic peroxide*	80-15-9	1-2

* This component is listed as a SARA Section 313 Toxic Chemical.

Ingredients which have exposure limits	ACGIH	OSHA	OTHER
Exposure Limits (TWA)	(TLV)	(PEL)	
Organic peroxide	None	None	1ppm(6mg/m3) Skin(WHEEL)

3. HAZARD IDENTIFICATION

Toxicity:	Liquid and Vapors are an eye and skin irritant.
Primary Routes of Entry:	None known
Signs and Symptoms of Exposure:	May cause dermatitis on prolonged contact in sensitive individuals.
Existing Conditions Aggravated by Exposure:	None

4. FIRST AID MEASURES

Ingestion:	Do not induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation:	Does not apply
Skin Contact:	Wash with soap and water.
Eye Contact:	Flush at least 15 minutes with plenty of water. Obtain medical attention.

5. FIREFIGHTING MEASURES

Flash Point:	More than 200°F
Extinguishing Agents:	Carbon dioxide, foam, dry chemical
Special Firefighting Procedures:	Not available
Hazardous Products formed by Fire or Thermal Decomp	Irritating organic vapors
Unusual Fire or Explosion Hazards:	None



MATERIAL SAFETY DATA SHEETS

TORQUE 170



6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case of spill or leak:

Soak up with an inert absorbent. Store in closed container until disposal.

7. HANDLING AND STORAGE

Safe Storage:
Handling:

Store at or below 100°F
Avoid prolonged contact with eyes and skin.

8. EXPOSURE AND PERSONAL PROTECTION

Eyes:
Skin:
Ventilation:
Respiratory

Safety glasses or goggles.
Neoprene, rubber, or butyl rubber gloves.
Does not apply
Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:
Odor:
Boiling Point:
pH:
Solubility in Water:
Specific Gravity
Vapor Pressure:
Vapor Density:
Evaporation Rate

Blue Liquid
Sharp, irritating
More than 300°F
Does not apply
Slight
1.1 at 25°C
Less than 0,5 mmbar at 20°C
Not available
Not available

10. REACTIVITY

Stability:
Hazardous Polymerization:
Incompatibility:
Conditions to Avoid:
Hazardous Decomposition
Products (non-thermal):

Stable
Will not occur
None
Not available
None

11. TOXICOLOGICAL INFORMATION

Estimated oral LD50 more than 10000 mg/kg.
Estimated dermal LD50 more than 5000 mg/kg.

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended methods of disposal:
EPA Hazardous Waste Number

Incinerate following EPA and local regulations.
NH - Not a RCRA Hazardous Waste Material



MATERIAL SAFETY DATA SHEETS

TORQUE 170



14. TRANSPORTATION INFORMATION

DOT (49 CFR 172)
Domestic Ground Transport
Proper Shipping Name:
Hazard Class or Division:
Identification Number:
Marine Pollutant:
IATA
Proper Shipping Name:
Class or Division:
UN or ID Number:

Unrestricted
Unrestricted
None
None
Unrestricted
Unrestricted
None

Engineering Excellence

For technical information
and support call **1-800-552-0299** or visit our website at

www.instantca.com